

BENEFITS

- Rotary and laser engraving and cutting
- Perfect material for UV printing
- Excellent for signage
- Can also be used as a substrate



APPLICATIONS

Interior and exterior signage, visual communication, decoration, gifts, promotional items, architectural models, trophy and award...

SPECIFICATIONS

Finish	Matt, Glossy or Frosted
Composition	Acrylic
Engraving depth	-
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	On demand

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	-
Break resistant	■
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

A real alternative to glass.

Frosted and matt white are fingerprint resistant.

For even more colours and possibilities, combine Acrylic with Gravotac™ Exterior (p 23).

Clear

Clear	3 mm (1/8")	83423
	6 mm (20")	83424
	10 mm (40")	83425
Translucent green	3 mm (1/8")	83426
	6 mm (20")	83427
Translucent blue	3 mm (1/8")	83428
	6 mm (20")	83429

Frosted

White	3 mm (1/8")	83431
Light blue	3 mm (1/8")	83434
Sky blue	3 mm (1/8")	83438
Blue ocean	3 mm (1/8")	83435
Blue lagoon	3 mm (1/8")	83437
Green	3 mm (1/8")	83436
Yellow	3 mm (1/8")	83432
Pink	3 mm (1/8")	83439
Mauve	3 mm (1/8")	83433

Fluorescent

Yellow	3 mm (1/8")	83428
Orange	3 mm (1/8")	83430
Pink	3 mm (1/8")	83429

Opaque

White	3 mm (1/8")	83440
	6 mm (20")	83441
Black	3 mm (1/8")	83442
	6 mm (20")	83443

